

SELF CONTAINED DROP-IN BASIN

Specifications

Drop-in Basin Only

Dimensions: 31.5" L (77 cm) x 24" W (61 cm) x 21" H (53 cm) (*Length includes front portion with handle and height includes footrest*)

Shipping Dimensions (including skid): 48" L (122 cm) x 40.0" W (102 cm) x 29" H (74 cm)

Shipping Weight: 73 lbs (33 kg)

Net Weight: 43 lbs (20 kg)

Drop-in Basin with Cabinet

Dimensions: 33.5" L (85 cm) x 25" W (64 cm) x 15" H (38 cm) (*Length includes front portion with handle, height is cabinet height*)

Shipping Dimensions (including skid): 48" L (122 cm) x 40.0" W (102 cm) x 29" H (74 cm)

Shipping Weight: 121 lbs (55 kg)

Net Weight: 86 lbs (39 kg)

Cabinet Only

Dimensions: 24" L (61 cm) x 24" W (61 cm) x 15" H (38 cm)

Net Weight: 43 lbs (20 kg)

Basin Capacity: 3.75 US Gallons (14.2 liters)

Power Requirements: 120V AC, 15 Amp, 60HZ. A **separate and dedicated** 15 Amp GFCI protected circuit **MUST** be used for each Drop-in Basin.

Construction: Welded steel frame with veneered front wood panel. Note: Any cabinet enclosure must provide access to internal components

Basin: Highly chemical resistant ABS Plastic, pre-plumbed.

Jet System: One (1) Dual Stream No Pipe™ Jet. Removable screen, no recirculating pipes. ON/OFF controlled by air-activated switch.

IMPORTANT: The Drop-in Basin MUST be installed by a licensed electrician and a licensed plumber in accordance with all national, state and local codes/regulations.

PLUMBING

Incoming: Hot/Cold supply lines required (1/2" ID).

Sprayer/Filler: Inline back-flow prevention is provided.

Discharge: Gravity drain or optional factory installed drain pump. If factory installed drain pump is utilized, built-in back flow prevention is provided.

NOTE: If through floor installation is desired, refer to Plumbing Rough-in drawing (available at ContinuumFootspas.com). See Owners Manual for complete installation instructions.

ON/OFF controlled by air activated switch. Drain Pump (optional, factory installed) ON/OFF controlled by air activated switch.

Certification: Underwriters Laboratories Listed  us Compliance Listings to the following Standards:

UL 1951, CAN/CSA C22.2 No. 68-92,

ANSI/ASME A112.18.3M, A112.19.7M, A112.18.1, CSA B125.1.2005

Compliant with IAPMO Plumbing Standards. Fixtures and hoses are UPC compliant.

Limited Warranty: One (1) year parts from date of shipment. **See Limited Warranty in Owner's Manual for complete details**

ACCESSORIES:

Deluxe Tech Chair: Base: 24" diameter (61 cm) Height range (excluding cushion): 13" to 16" (33 cm to 41 cm)

Net weight: 15 lbs (7 kg)

Shipping Dimensions: 26" W (66 cm) x 26" L (66 cm) x 12" H (31 cm) Shipping Weight: 23 lbs (11 kg)

Standard Tech Chair: Base: 21" diameter (53 cm) Height range (including cushion): 14" to 16.5" (36 cm to 42 cm)

Net weight: 14 lbs (6 kg)

Shipping Dimensions: 21" W (53 cm) x 21" L (53 cm) x 11" H (28 cm) Shipping Weight: 18 lbs (8 kg)

Accessory Cart: 24" L (61 cm) x 19" W (48 cm) x 20" H (51 cm) Net Weight: 32 lbs (15 kg)

Shipping Dimensions: 26" W (66 cm) x 26" L (66 cm) x 12" H (31 cm) Shipping Weight: 35 lbs (16 kg)

Note: Due to continuous improvements, all specifications are subject to change without notice. All dimensions and weights are approximate.