

BRAVO® LE/VE MODEL

Specifications

Unless Specifically Noted, Specifications refer to both LE and VE Models.

Overall Dimensions: Bravo LE – 55.75”L (141.6 cm) x 45.5” W (116 cm) x 56” H (142 cm)

Bravo VE – 55.75”L (141.6 cm) x 45.5”W (116 cm) x 52”H (132 cm) – Refer to Installation Drawings for additional details.

Dimensions Seat to Floor: 24” (61 cm)

Suggested Minimum Distance from Back Edge of Spa Base to Back Wall: Bravo LE – 19” (48 cm) Bravo VE – 22” (56 cm)

Refer to Installation Drawings for additional details.

Shipping Dimensions Including Skid: 68” L (173 cm) x 34” W (86 cm) x 44” H (112 cm)

Shipping Weight Including Skid: Bravo LE – 315 lbs. (143 kg) / Bravo VE – 338 lbs. (153 kg)

Shipping Dimensions (Carton Size): 84.0” L (213 cm) x 40.0” W (102 cm) x 44” H (112 cm)

Net Weight: Bravo LE – 290 lbs. (132 kg) / Bravo VE – 313 lbs. (142 kg)

Client Weight Capacity: 350 lbs. (160 kg)

Basin Capacity: 4.75 US Gallons (18 liters)

Power Requirements: 120V AC, 15 Amp, 60HZ. A separate and dedicated 15 Amp GFCI circuit MUST be used for each pedicure chair.

Construction: Reinforced fiberglass with chemical resistant gel-coated finish.

Basin: Specially hardened and tempered glass, pre-plumbed.

Jet System: One (1) Dual Stream Magnetic Jet

IMPORTANT: Your Pedicure Chair MUST be Installed by a Licensed Electrician and a Licensed Plumber in Accordance with all National, State and Local Codes/Regulations.

PLUMBING:

Incoming: Hot/Cold supply lines required (1/2” ID). 1/2” MPT connections located on back of spa base.

Sprayer/Filler: Inline back-flow prevention is provided behind the mixing valve. Neoperl P/N 31.4015.0.

Discharge: Gravity drain is standard. Optional factory installed drain pump (air activated switch) with a 3/4” MPT connection located on back of spa base. Back flow prevention is provided.

MASSAGE: Full Function Shiatsu Back Massage with fold down manicure trays and hand held control wand.

CHAIR CONTROLS: Two (2) linear actuators electronically controlled with hand held wand. Forward/Backward/Recline.

Certification: Underwriters Laboratories Listed  Compliance Listings to the following Standards: UL 1951, CAN/CSA C22.2 No. 68-92, ANSI/ASME A112.18.3M, A112.19.7M, A112.18.1, CSA B125.1.2005

Compliant with IAPMO Plumbing Standards. Fixtures and hoses are UPC compliant.

LIMITED WARRANTY: Please refer to **Limited Warranty** in Owner’s Manual. Visit our website and MyContinuumPedicure.com.

ACCESSORIES:

Deluxe Tech Chair: Base: 19” diameter (48 cm) Height range (excluding cushion): 12” to 15” (30.5 cm to 38 cm)

Net weight: 15 lbs. (7 kg)

Shipping Dimensions: 26” W (66 cm) x 26” L (66 cm) x 12” H (31 cm) Shipping Weight: 23 lbs. (11 kg)

Standard Tech Chair: Base: 18” diameter (46 cm) Height range (including cushion): 12” to 18” (30.5 cm to 38 cm)

Net weight: 13 lbs. (6 kg)

Shipping Dimensions: 22” W (56 cm) x 30” L (76 cm) x 10” H (25 cm) Shipping Weight: 15 lbs. (7 kg)

Accessory Cart: 16” L (40.6 cm) x 13” W (33 cm) x 17” H (43 cm)-Height is from floor to working surface. Net Weight: 28 lbs. (12.5 kg)

Shipping Dimensions: 21” W (53 cm) x 19” L (48 cm) x 23” H (58 cm) Shipping Weight: 37 lbs. (16.5 kg)

Note: Due to continuous improvements, all specifications are subject to change without notice. All dimensions and weights are approximate.