



WALL-MOUNTED TEMPTURA ULTRA DRYER



The Collins Wall-Mounted TempTura Dryer features a large hood, variable time and temperature settings, and 1000 watts of drying power. The down draft operation doesn't require a hair net be used on clients. Sturdy U shaped base design offers better stability and makes the dryer much easier to roll behind salon chairs than other models. ETL listed.

Requires in-the-wall reinforcement for installation.

TECHNICAL INFORMATION

- ETL listed to UL 1727:2012 in US and CSA C22.2#36:2008 in Canada
- Down-draft dryer w/ smoked hood
- Variable time and Temperature settings
- Cool-down cycle
- Oversized hood measure 12.5" inside diameter
- 17.5" Diameter at largest point
- 110 volts
- 1000 watts
- Articulating arm w/ 5'4" diameter reach
- Arm measures 35" fin wall to elbow, 29" elbow to dryer
- 6-foot-long power cord
- No hair net needed

SHIPPING INFORMATION

Item generally ships via Parcel (Fedex/UPS) service

- Weight: 45 lbs
- Dimensions: 2 cartons

WARRANTY

5 Years:

- Collins 2200 Sol-Air dryer motors & hoods

2 Years:

- Jeffco K500 Complete and Collins 2200 Remaining components

1 Year:

- All remaining dryer and processor models and components

All warranties are part replacement warranties only with labor being provided by the customer. The factory technicians will help diagnose the problem by phone or video conference and ship out the replacement component. Technicians will also provide any instructions for repair as well.



PRODUCT SPECIFICATION SHEET



Part #: 1433H
Description: Collins Wall-Mounted TempTura Ultra Dryer

Standard Features:

- Down-draft dryer w/ smoked hood
- Variable time & temperature settings
- Cool-down cycle
- Oversized hood measures 12.5" inside diameter & 17.5" diameter at largest point
- 110 volts & 1000 watts
- Well engineered articulating arm with 5'4" diameter reach
- Arm measures 35" from wall to elbow, 29" elbow to dryer
- No hair net needed!



Specifications:

Collins Wall-Mounted TempTura Ultra Dryer wall-mounted version w/ engineered articulating arm. Arm measures 35" from wall to elbow, plus 29" from elbow to dryer. Provides 5' 4" diameter semi-circle-shaped working range from mounting bracket. Unit installs 78" from the floor ... **IN-THE-WALL BACKING or OVERLAY PANEL REQUIRED TO SPAN MULTIPLE STUDS.** Hair net not needed.

Shipping and Assembly/Installation Information

Assembly Required: Yes
Electrical Required: Yes
Plumbing Required: No
Ship Dimensions
Total Ship Weight 42 LBS
of Ship Pieces 2 Cartons Skids

Additional Information:

No hair net needed!

